



Cup filling-sealing



**MACHINES**

[www.cemremakina.com](http://www.cemremakina.com)

CEM-1

## Conditionneuse du yaourt en pots

Stations of machines

- 1- Cup dropping
- 2- Filling station
- 3- Alu-lid placing ( pre-cuted lid)
- 4- Sealing
- 5- Dating
- 6- Exit conveyor



### SOME SPECIFICATIONS

- |                    |                                      |
|--------------------|--------------------------------------|
| - MODEL            | : Cem-1 rotary new model             |
| - CAPACITY         | : 1500 psc / per hour min. capacity. |
| - CUPS SIZE        | : Your cup size                      |
| - FILLING PRODUCTS | : Yogurt                             |
| - FILLING RANGE    | : from 50 to 250 gramme.             |
| - DIMENSIONS       | : 1100 x 1100 x 2000 mm appr.        |
| - WEIGHT           | : 350 Kg appr.                       |
| - PACKING          | : Wooden Chest                       |
| - ELECTRICAL       | : Relay system 380 V.                |

# Conditionner du yaourt en pots

The machine has third photocell check-points

-First photocell to control for filling if there is any cup or not Thanks to this photocell system, the machine would not waste the product. If there is no cups, then the machine would not fill.

- Second photocell to control for filling if there is any cup or not Thanks to this photocell system, the machine would not waste the product. If there is no cups, then the machine would not fill.

-Third photocell control for the aluminum lids if there is no cup or not, thanks to this system if there is no cup then the machine would not waste the aluminum lids

## GENERAL OPERATING OF THE MACHINE STATIONS

<u>ROTARY TABLE</u>	: Rotary Table turns by mechanical indexer.
<u>CUP DROP STATION</u>	: plastic cups dropping by pneumatical
<u>FILLING STATION</u>	: Filling station work by volumetric(pump). filling funnel capacity 40 litre appr. accuracy in filling is about %2. Filling station could fill high visicocity yogurt.
<u>PLACING LID STATION</u>	: Lids on magazine are Putting on cups by vacuuming pneumatical
<u>SEALING</u>	: Lids are sealed to cups by heat pneumatical
<u>DATING</u>	: The machine dates by ink. Two-line dating is available
<u>EXIT</u>	: Cups are taken up to outlet conveyor. Lengh is

## nouveaux modèles 2015 Conditionneuse Yaourt

